



TL - 12SS

Pressure Reducing Valve Full Port Flanged End


Materials : ASTM A351-CF8 Steam / Air Size : 1/2" ~ 4"

TL - 13 / 14

Pressure Reducing Valve Full Port Flanged End

Materials : Cast Iron Steam / Air

Size : 1/2" ~ 6"



Working Condition

- 1- Working pressure : 1-10 kg/cm²
- 2- Working temperature : 200 °c
- 3- Medium : Steam

ANSI - 150LB Dimensions

MM	INCH	L	D	C	B	H1	H2	H	N	KG
15A	1/2"	155	89	60.5	15	74	260	15	4	10
20A	3/4"	155	98	70	20	74	260	15	4	10.5
25A	1"	165	108	79.5	25	74	260	15	4	11
32A	1 1/4"	195	117	89	32	99	280	15	4	16
40A	1 1/2"	195	127	98.5	40	99	280	15	4	17
50A	2"	225	152	120.5	50	116	310	19	4	24
65A	2 1/2"	250	178	139.5	65	125	322	19	4	31
80A	3"	290	190	152.5	80	135	325	19	4	37
100A	4"	330	229	190.5	100	153	370	19	8	50
125A	5"	410	254	216	125	195	540	22	8	98
150A	6"	410	279	241.5	150	195	540	22	8	105

PN16-DIN-2633 Dimensions

MM	INCH	L	D	C	B	H1	H2	H	N	KG
15A	1/2"	155	95	65	15	74	260	14	4	10
20A	3/4"	155	105	75	20	74	260	14	4	10.5
25A	1"	165	115	85	25	74	260	14	4	11
32A	1 1/4"	195	140	100	32	99	280	18	4	16
40A	1 1/2"	195	150	110	40	99	280	18	4	17
50A	2"	225	165	125	50	116	310	18	4	24
65A	2 1/2"	250	185	145	65	125	322	18	4	31
80A	3"	290	200	160	80	135	325	18	8	37
100A	4"	330	220	180	100	153	370	18	8	50
125A	5"	410	250	210	125	195	540	18	8	98
150A	6"	410	285	240	150	195	540	22	8	105

UNIT M/M